

POLY SEALERS & SEALS

POLYESTER & POLYPROPYLENE



EP-1200 ECONOMY FRONT ACTION SEALER

- Polypropylene strapping
- Size Options: 1/2", 5/8", 3/4"
- Use snap-on open seals (P12S01, P12S02, P58S02, P34S02)



EP-1225 PREMIUM FRONT ACTION SEALER

- Polypropylene strapping
- Size Options: 1/2", 5/8", 3/4"
- Use snap-on open seals (P12S01, P12S02, P58S02, P34S02)



EP-1235 BIDIRECTIONAL FRONT ACTION SEALER

- Polyester strapping
- Size Options: 1/2", 5/8", 3/4"
- 17" handles on 1/2" & 5/8"
- 25" handles on 3/4"
- Use serrated seals (P12SS3, P58SS3, P34SS3)



POLY SEALERS & SEALS

POLYESTER & POLYPROPYLENE



EP-1245 SYMMETRICAL SEALER

- Polyester strapping
- Size Options: 5/8", 3/4"
- 17" handles
- Use symmetrical seals (P58SY4, P34SY4, P34SY6)



EP-1250 UNIDIRECTIONAL PREMIUM FRONT ACTION SEALER

- Polyester strapping
- Size Options: 1/2", 5/8", 3/4"
- 17" handles on 1/2" & 5/8"
- 25" handles on 3/4"
- Blue: long jaw | Orange: short jaw
- Use serrated seals (P12SS3, P58SS3, P34SS3)



EP-1255 ECONOMY POLYESTER SEALER

- Polyester strapping
- Size Options: 5/8"
- 17" handles
- Use serrated seals (P58SS3)



POLY SEALERS & SEALS

POLYESTER & POLYPROPYLENE



EP-1275 HD PREMIUM FRONT ACTION MICRO-GRIT SEALER

- Polyester & Polypropylene strapping
- Size Options: 1/2", 5/8"
- Use micro-grit seals (P12PS3, P58PS4)



EP-1285 SERRATED PUSHER SEALER

- Polyester & Polypropylene strapping
- Size Options: 1/2", 5/8", 3/4"
- Use serrated pusher seals (P12PO3, P58PO3, P34PO3)



EP-1295 HD SIDE ACTION MICRO-GRIT SEALER

- Polyester strapping
- Size Options: 5/8", 3/4"
- Use micro-grit seals (P58PS4, P34PS4)



POLY SEALERS & SEALS

POLYESTER & POLYPROPYLENE



EP-1260 HD FRICTION WELDER - POLYPROPYLENE

- Polypropylene strapping
- Strap Range: 1/2-3/4"
- Strap Thickness: up to 0.060"
- $\geq 80\%$, when properly set
- No seals needed!
- Battery operated (sold separately)



EP-1265 HD FRICTION WELDER - POLYESTER

- Polyester strapping
- Strap Range: 1/2-3/4"
- Strap Thickness: up to 0.060"
- $\geq 80\%$, when properly set
- No seals needed!
- Battery operated (sold separately)



EP-1270 HD FRICTION WELDER - PP/POLY

- Polyester & Polypropylene strapping
- Strap Range: up to 1 1/4"
- Strap Thickness: up to 0.060"
- $\geq 80\%$, when properly set
- No seals needed!
- Battery operated (sold separately)



POLY SEALERS & SEALS

POLYESTER & POLYPROPYLENE



EP-1355 HD BATTERY TOOL

Polypropylene Strapping	Polyester Strapping
Strap Width: 1/2 - 5/8"	Strap Width: 5/8 - 3/4"
Strap Thickness: up to .026 - .05"	Strap Thickness: up to .028 - .05"
Break Strength: up to 425 lbs	Break Strength: up to 925 lbs
Tension Range: 55 - 551 lbs	Tension Range: 88 - 881 lbs
Includes: 1 charger & 2 batteries	(Tool hanger sold separately)

